

# Vessels Bound To & From Sir Baniyas Island Cruise Terminal

Approved by:



**Rashed Saud Al Shamsi**  
Director, Business and Commercial Support

## Document Ownership

ADNOC Business and Commercial Support Directorate (B&CSD) shall be the custodian of this document. B&CSD shall ensure that the current version of this document is made available to all concerned.

ADNOC Petroleum Ports Authority (PPA) is the owner of this document and shall be responsible for initiating any required changes to the document. Any and all approved changes shall be incorporated by re-issuing the document at the next revision with a revision number.

Any inconsistency/discrepancy with the International Best practices, International/Local legislations, UAE Federal Laws if noted shall immediately be brought to the attention of PPA. Authority for the interpretation contained in this procedure is vested in ADNOC Petroleum Ports Authority.

Any recommendation for the continuous improvement is to be submitted to B&CSD via PPA, who has the sole right to approve and circulate revisions for implementation accordingly.

## Review History

DATE	REV. NO.	DESCRIPTION	REFERENCE SECTION

## Revision History

DATE	REV. NO.	DESCRIPTION	REFERENCE SECTION

<b>Prepared By</b>	Capt. Rohit Abrol	March-2017
<b>Reviewed By</b>	Eng. Ali Asad Abubaker	March-2017
<b>Endorsed By</b>	Capt. Jasim Al Khamiri	March-2017

## © Petroleum Ports Authority

No part of this document may be reproduced, utilized, stored in any retrieval system or transmitted in any form or by any means, electronic or mechanical, including photocopying, recording or by any information, storage or retrieval system without the written permission of ADNOC Petroleum Ports Authority. Any electronic or printed copies are uncontrolled.

For the current version of this document please visit <https://ppa.adnoc.ae>

## Table of Contents

<b>1.</b>	<b>INTRODUCTION.....</b>	<b>4</b>
1.1	OBJECTIVES .....	4
1.2	SCOPE .....	4
<b>2.</b>	<b>GLOSSARY .....</b>	<b>4</b>
<b>3.</b>	<b>REQUIREMENTS/RECOMMENDATIONS/RESPONSIBILITIES .....</b>	<b>4</b>
<b>4.</b>	<b>RECORDS.....</b>	<b>5</b>

## 1. INTRODUCTION

### 1.1 Objectives

This procedure ensures Safety of the Passenger vessels calling at Sir Baniyas Cruise terminal.

### 1.2 Scope

This procedure applies to Passenger vessels bound to/from Sir Baniyas Cruise Terminal.

## 2. GLOSSARY

Term	Definition
<b>ADNOC</b>	Abu Dhabi National Oil Company
<b>IMPA</b>	International maritime Pilot's Association
<b>PPA</b>	Petroleum Port Authority
<b>SOLAS</b>	Safety of Life At sea
<b>U.K.C</b>	Under Keel Clearance
<b>VHF</b>	Very High Frequency
<b>VTIS</b>	Vessel Traffic Information service

## 3. REQUIREMENTS/RECOMMENDATIONS/RESPONSIBILITIES

- i. All vessels bound to/from the Sir Baniyas Cruise Terminal are subject to compulsory pilotage and will carry an authorized Pilot for the entire passage from the East Ghasha Pilot Station to/from the anchoring/mooring position.
- ii. All Cruise vessels shall, where weather conditions permit, be boarded at the East Ghasha Pilot station. Master of the vessel shall ensure that the Pilot boarding arrangements are as per IMPA's/ SOLAS Chapter V/23 requirements. The Pilot shall board in sufficient time to arrive as scheduled at the Sir Baniyas Cruise Terminal.
- iii. An outline passage plan from Ghasha pilot Station up to the terminal shall be completed by the Pilot and fully discussed with the Master. The vessel shall be boarded early enough to allow sufficient time to discuss the passage plan with the Master. The vessel's Master must make the Pilot aware of any peculiarities of the vessel especially with regard to maneuvering characteristics.
- iv. Subject to the Harbour Master discretion, an Escort tug shall be provided for inward and outward transit of all passenger vessels from/up to south of Latitude 24 Deg 22'N.
- v. Abort points/ areas shall be highlighted during the Master Pilot exchange. In the event that a decision is taken to abort the passage, VTIS shall be informed of the situation and VTIS shall in turn notify the Harbour Master.
- vi. To ensure safe channel passage a minimum U.K.C is required for all ships entering or leaving the port as follows:
  - Up to 100,000 SDWT UKC 0.92 meters / 3 Feet
  - Up to 250,000 SDWT UKC 1.22 meters / 4 Feet
  - Up to 350,000 SDWT UKC 1.52 meters / 5 Feet
  - Over 350,000 SDWT UKC 1.83 meters / 6 Feet

Such under keel clearance may be increased at any time at the Port Authority's discretion having due regard to the weather condition. Squat allowances and the limit of the tide table accuracy shall be taken into account prior to allowing a vessel to call at the Sir Baniyas terminal.

- vii. Navigation within the Port limits is not allowed in visibility less than 1.0 Nautical Mile and Berthing/ Un berthing is not allowed in visibility less than 0.5 Nautical Mile, Vessel shall await instructions from the VTIS/Port Control in this case.
- viii. Vessels using the Sir Baniyas Cruise Terminal shall monitor VHF Channel 21/09 & 16 at all times.
- ix. Local weather forecasts shall be monitored by the Master of the vessel at all times to remain fully appraised of the situation.
- x. Prior to arrival of any passenger vessel, Sir Baniyas Cruise terminal manager shall formulate a mooring plan in consultation with the assigned pilot, He shall then submit the plan to the Harbour Master Jebel Dhanna Ruwais. After Harbour Master's approval, the mooring plan shall be conveyed to the vessel and the facility. Any changes requested by the Master and agreed by the Pilot shall be forwarded to the Harbour Master Jebel Dhanna Ruwais for his approval.
- xi. Throughout the period of time that the vessel is moored at Sir Baniyas Cruise Terminal, prevailing and forecasted weather conditions shall be continually monitored by VTIS and Ships Master. If winds in excess of 35 knots are forecast, then the vessel moored at the Sir Baniyas Island shall be informed and additional moorings shall be paid out as required. If deemed necessary, a pilot should be called to attend the vessel, and arrangements should be made for any required stand-by tugs to attend, The vessel's Master shall ensure that Engines, steering and thrusters (if available) are readied for immediate use, and that the vessel is ready to un berth and depart should the need arise.
- xii. In winds of more than 35knots from a direction of North East (NE) or South East (SE), or sustained winds of 40 knots from any direction, the Master in consultation with the assigned pilot and Terminal shall assess the conditions and halt passenger operations if he considers it unsafe to continue. Any additional tugs shall be called as required by the Master in consultation with the pilot. If passenger operations are halted due to stress of weather, they shall not resume until the Master, in consultation with the Pilot and Terminal, decides it is safe to do so.
- xiii. Pilot and tugs may be released from the vessel in agreement with the Master and in consultation with the Sir Baniyas Island Manager/Harbour Master.
- xiv. By virtue of attendance, the Pilot, Pilot boat, Tugs, crafts and any other personnel or equipment involved in serving the Vessel shall be considered as the "servants" of the Vessel Owner. The Vessel Owner shall be liable for any wrongful acts committed by those servants during the course of their employment, whether or not the Master of the vessel has authorized them.
- xv. Priority of transit is typically granted to the commercial vessels calling at Jebel Dhanna Ruwais Port for loading and/or discharging cargo. Particular priority is granted to the deep draft loaded vessels. However, in view of the sensitivity of the vessels carrying Passengers, and the limited time available on their schedule, subject to traffic density, and at the discretion of the Harbor Master, priority for transiting in and out may be granted to the Passenger Vessels.
- xvi. Cruise Vessels shall use East Ghasha Channel for Inbound/Outbound passages, However under exceptional circumstances they may be allowed to use Ruwais Channel for inbound and/or Yas channel for outbound passages at Harbour Master's discretion.
- xvii. Passenger Vessel's up to Length Overall of (200) meters shall anchor in Anchor Position (A1) and vessels above (200) meters Length overall shall anchor in Anchor position (A2) as delineated on BA chart 3780.

#### 4. RECORDS

The approved Mooring plans for passenger vessel's shall be retained by the Harbour Masters electronically for a period of one year.